



SINO  
COLOR



# A3/A2 DTG T-Shirt Printer



Direct to Garment

Super Reliable

超穩定

White Circulation

白墨循环

High Speed

速度快

Easy to Use

易于使用


# A3 DTG Printer | TP-300 & TP-600 Series

## • Features



### SinoColor System

Much more professional and more stable than desktop modified printer. Control the color freely.



### White Ink Circulation and Stirring System

Reduce problem caused by White ink precipitation.



### Well-Designed Touch Screen

Easily adjust platform position.



### Auto Media Height Detecting

Automatic media height detecting system is standard equipped. Simplify the setting of proper platform height.



### Professional Design

Maximumly use mold to produce machine components to achieve amazing resolution.



## • Specification

| Model No.                       | TP-300i  | TP-300D                   | TP-600i      | TP-600D                    |
|---------------------------------|--|---------------------------|--------------|----------------------------|
| Printhead                       | 1×Epson Head   | 2×Epson i1600 Heads       | 1×Epson Head | 2×Epson i1600 Heads        |
| Resolution                      | 1440dpi  | 2400dpi                   | 1440dpi      | 2400dpi                    |
| Ink Color                       | CMYK   | CMYK + W                  | CMYK         | CMYK + W                   |
| Max Speed                       | 2 minutes for one T-shirt  |                           |              |                            |
| Print Head Height               | 10 cm Max  |                           |              |                            |
| Printing Size                   | 30×40 cm Max   |                           | 40×60 cm Max |                            |
| Print Direction                 | Intelligence double side   |                           |              |                            |
| Print Method                    | Micro piezo print technology, intelligence drops transformation technology         |                           |              |                            |
| Height Adjust                   | Electric   |                           |              |                            |
| Distance of Print Head Printing | 1-3 mm (2 mm is the best)  |                           |              |                            |
| Ink Supply System               | CISS   |                           |              |                            |
| Ink Consumption                 | 15-20 ml / squire meter (1 liter print about 300PCS T-shirt)                       |                           |              |                            |
| Min Ink Drop Size               | < 1.5 PL   |                           |              |                            |
| Interface                       | USB 3.0  |                           |              |                            |
| Rip Software                    | Maintop (Standard) / FlexiPRINT (Optional)   |                           |              |                            |
| Working Environment             | Temperature 18-30 Celsius, Humidity 30-70 RH, Clean room, Low dust, Less sun light |                           |              |                            |
| Power                           | AC 110/ 220V, 50/ 60Hz, 300W   |                           |              |                            |
| Size & Weight                   | Machine  | L820×W740×H560 mm / 82KG  |              | L1070×W860×H560 mm / 110KG |
|                                 | Packing  | L900×W840×H710 mm / 100KG |              | L1150×W950×H680 mm / 140KG |

Specifications are subject to change without notice.